

# PC-45

## 450mm 6 Basket Pasta Cooker



# PROFESSIONAL

### Specifications

- NAT Gas: 63 MJ/h, LP Gas: 63 MJ/h
- Supplied with gas regulator (specify NAT or LP on order)
- Gas Inlet: 3/4" BSP Male
- 180mm from Right, 70mm from Rear, 150mm from Floor
- Water Inlet: 1/2" BSP Male
- 60mm from Left, 70mm from Rear, 80mm from Floor
- Drain: 1" ID Hose
- 225mm from Left, 210mm from Front, 220mm from Floor
- Working Height: 900mm
- Dimensions: 450 x 800 x 1100H @ 74kg
- Packed Dimensions: 640 x 860 x 1260H @ 94kg
- Heavy duty construction with 304 stainless steel panels
- Stainless steel feet with 55mm height adjustment range

### Pasta Cooker

- 63 MJ/h jet burner with pilot, FFD and piezo ignition
- Adjustable thermostat accurately controls water temperature
- Water purifying overflow system to remove excess starch
- High temperature cut-out safety mechanism
- Marine grade 316 stainless steel tank
- Fiberfrax Durablanket insulation on both sides of tank
- 35 litre tank capacity
- Stainless steel tank filter and drain back basket stand
- Rear laundry arm with controls located on front panel
- Includes 6 perforated stainless steel baskets
- Safety release tank drainage valve at bottom of unit

### Cleaning & Servicing


- Easy access to all parts & components from front
- Removable baskets and inserts

### Options/Accessories

- Rear Castors (rigid)
- Front Castors (swivel with brakes)
- Joining caps
- LH & RH side shields

### Warranty

- 1 Year Included + 1 Year Extendable upon registration



Must be installed by an authorised person in accordance with AS/NZS 3000.

Please note that specifications or design may be altered at any time without notice.

Luus Industries Pty Ltd | +61 3 9240 6822 | sales@luus.com.au | www.luus.com.au

